



## Flashing Membrane, House and Stucco Wrap and Sheathing Tape

### FLASHING MEMBRANE

A nonwoven mat facer and self-sealing rubberized asphalt membrane that functions as a moisture and air barrier.

- 40 mils (1.0mm) thick and black in color. It can be applied to various substrates such as wood, metal, gypsum sheathing and to Dupont® Tyvek® StuccoWrap™ and other code-conforming weather resistive barriers.
- Functions as a seal and flashing at sills of rough openings, deck framing, etc., interfacing with the building substrate and other code-conforming weather resistive barriers.

#### Unit Size:

- 3 inches x 100 feet (7.6cm x 30.5m) Rolls per Box 12
- 6 inches x 100 feet (15cm x 30.5m) Rolls per Box 8
- 12 inches x 100 feet (30cm x 30.5m) Rolls per Box 4
- Sold only by the box

#### Thickness:

40 mil (1.0mm). Elongation (Rubber Asphalt Adhesive) over 500% ASTM-D-412. Moisture Vapor Transmission Rate: 0.1 perm max. ASTM-E-96.

### HOUSE WRAP

House Wrap is a Grade D vapor permeable, asphalt impregnated sheathing paper providing moisture protection.

- This 60 Minute Asphalt saturated Kraft sheathing paper conforms to Federal Specification UU-B-790a Type 1 Grade D Style 2, accepted by Uniform Building Code and ICBO Evaluation Report No. 1025. It is easily installed and is designed for use as a weather resistive barrier behind EIFS insulation board.

#### Unit Size:

- 40 inches x 72 feet (101.6cm x 22m). Roll is 240 sq. ft. (22m<sup>2</sup>)

### STUCCOWRAP™

StuccoWrap™ is a Dupont® Tyvek® material with engineered drainage channels. It offers protection against moisture intrusion and provides a means of drainage should water ingress occur. StuccoWrap is used with flat EPS board in the El Rey Insul-Flex® with StuccoWrap system providing an effective EIFS drainage solution. StuccoWrap is suitable for use with wood sheathing.

#### Unit Size:

- 5 feet x 200 feet (1524mm x 61m), Roll is 1000 sq.ft.
- 9 rolls per box
- 4 boxes per pallet

#### Air Penetration: >300 TAPPI T-460

- Water Vapor Transmission: 50 perms; ASTM E-96 Method B
- Water Penetration Resistance: >210cm AATCC-127



**SHEATHING JOINT TAPE**

**Description and Use:**

Non-woven fabric used to tape the joints of the sheathing boards to which the roll-on weather barrier is applied

**Coverage:**

Approximately 750 linear ft. (229m) of wall area per roll

- One roll of sheathing joint tape can tape the joints of approximately 2,000 sq.ft. (185.8 m<sup>2</sup>) of wall area sheathed with 4 ft. (1.2m) by 8 ft. (2.4m) sheathing.

**Packaging:**

Roll, 4 inches (102mm) wide by 750 feet (229m) long

**Job Name** \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

**Contractor** \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

**Date** \_\_\_\_\_

**Submittal Approvals:** \_\_\_\_\_

**Stamps or Signatures** \_\_\_\_\_



[www.elrey.com](http://www.elrey.com)

**El Rey Sales Office**

3830 Singer Blvd. NE  
Suite 2020  
Albuquerque, NM 87109  
Phone: (505) 873-1180  
Fax: (505) 345-9009

**Albuquerque Plant**

4100 1/2 Broadway SE  
Albuquerque, NM 87105  
Phone: (505) 873-1181  
Fax: (505) 877-6670

**Colorado Springs Plant**

3225 S. Drennan Industrial Loop  
Colorado Springs, CO 80910  
Phone: (719) 392-9003  
Fax: (719) 392-6346

**Corporate Office  
ParexLahabra, Inc.**

4125 E. La Palma, Suite 250  
Anaheim, CA 92807  
Phone: (714) 778-2266  
Fax: (714) 774-2079