



MATERIAL SAFETY DATA SHEET

MANUFACTURER: PAREXLAHABRA, INC.
EI REY STUCCO
ADDRESS: 4100^{1/2} BROADWAY S.E.
ALBUQUERQUE, NM 87105
TELEPHONE: (505) 873-1181

Date: March 13, 2002

Page 1 of 4

IN CASE OF SPILL EMERGENCY, DAY OR NIGHT, CALL CHEMTREC 1-800-424-9300

SECTION I

PRODUCT IDENTIFICATION

IDENTITY: COLOR SEAL™

SECTION II

COMPOSITIONAL INFORMATION

<u>Ingredients</u>	<u>CAS Req No.</u>	<u>APPROX. WT.%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>
Vinyl Acrylic Resin	NON HAZ	10.0 max	n.a.	n.a.
Hydrous Alum Silicates	1332-58-7	14.0 max	10.0mg/M ³	10.0mg/M ³ *
Silica, Amorphous	7631-86-9	1.3 max	10.0mg/M ³	6.0mg/M ³ *
Silica, Crystalline	14808-60-7	2.1 max	0.1mg/M ³	0.1mg/M ³ *
Inorganic Filler	1317-65-3	34.0 max	10.0mg/M ³	5.0mg/M ³ *
Titanium Dioxide	13463-67-7	13.0 max	5.0mg/M ³	5.0mg/M ³ *
Ethylene Glycol	107-21-1	2.5 max	50.0ppm	n.e.
Water	NON HAZ	60.7 max	n.a.	n.a.

*Respirable dust

SECTION III

PHYSICAL PROPERTY INFORMATION

Boiling Point:	n.a.
Freezing Point:	n.a.
Viscosity (KU):	95±3
Vapor Pressure (mm Hg):	n.a.
Vapor Density (air=1):	Greater than 1
Density (lb./gal.):	10.5 - 12.1
Volatile Volume (%):	61.6 - 75.5
Evaporation Rate (Ether = 1):	Less than 1
Volatile Organic Compounds, VOC (g/l):	< 250

SECTION IV

FIRE AND EXPLOSION HAZARD INFORMATION

Flammable Classification:	Not regulated.
Flash Point (Method):	>250°F PMCC

MATERIAL SAFETY DATA SHEET – COLOR SEAL™
EL REY STUCCO

SECTION IV (continued)

FIRE AND EXPLOSION HAZARD INFORMATION

Flammable Classification: Not regulated.

Flash Point (Method): >250°F PMCC

Flammable Limits: LEL: n.a.

UEL: n.a.

Extinguishing Media: Foam, CO₂, dry chemical and water fog.

Special Fire Fighting Procedures: Cool exposed containers with water. Use self-contained breathing apparatus.

Unusual Fire and Explosion Hazards: Closed containers may burst, if exposed to extreme heat or fire. Toxic gases may form when product burns.

SECTION V

HEALTH HAZARD INFORMATION

EFFECTS OF OVEREXPOSURE

Inhalation: Irritation of the respiratory tract.

Eye and Skin Contact: Irritating to skin upon repeated or prolonged contact. Irritating to eyes.

Ingestion: Ingestion of large amounts could cause serious injury.

Chronic Effects of Exposure: Sanding dust inhalation may cause lung damage. Crystalline silica has been classified as probably carcinogenic for humans' (2A) by IARC.

Medical Conditions Prone To Aggravation By Exposure: None expected when used in accordance with Personal Protection Information (Section VIII).

EMERGENCY AND FIRST AID PROCEDURES

Inhalation: Remove to fresh air. Get medical help for any breathing difficulty.

Eye Contact: Flush thoroughly with water. Call Physician.

Skin Contact: Wash with soap and water.

Ingestion: Drink 1 to 2 glasses of water to dilute. Do NOT induce vomiting. Call a physician.

HAZARDOUS RATING: (for material as packaged)

Health/Toxicity

1

Flammability

0

Reactivity

0

Personal Protection

B

SCALE;

4 = Sever

3 = Serious

2 = Moderate

1 = Slight

0 = Minimal

NOTE: HMIS, NFPA, and El Rey ratings involve data and interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

SECTION VI

REACTIVITY INFORMATION

Stability: Stable under normal conditions.

Incompatibility: None

**MATERIAL SAFETY DATA SHEET – COLOR SEAL™
EL REY STUCCO**

Page 3 of 4

SECTION VI (continued)

REACTIVITY INFORMATION

Hazardous Decomposition or Byproducts: Temperatures above 177°C/350°F may cause the vinyl acrylic resin to decompose. There are no hazardous byproducts. Burning may produce carbon dioxide and carbon monoxide.

Hazardous Polymerization: Will not occur.

SECTION VII

SPILL OR LEAK PROCEDURE INFORMATION

Keep spectators away as area of leak or spill may be slippery. The spilled materials may be scooped into pails; the remaining material may be taken out of the surface by absorbing it with sand, earth or any other inert material. If needed, the floor can be flushed with plenty of water. All materials (product and absorbing medium) should then be disposed of in accordance with pertinent Federal, State and Local Government Regulations. Take extra care so that none of the cleaning waters gets into sanitary water sewers or storm drains.

SECTION VIII

PERSONAL PROTECTION INFORMATION

Respiratory Protection: Use NIOSH approved respirator specified for protection against paint spray mist and sanding dust in restricted or confined areas.

Protective Gloves: Waterproof during repeated contact.

Eye Protection: Splash goggles or safety glasses with side shields.

Ventilation: Adequate to maintain working atmosphere below TLV and LEL, see Section II for ingredient data and concentrations. Mechanical exhaust may be required in confined areas.

Other Protective Equipment: Clothing adequate to protect skin.

Hygienic Practices: Remove and wash clothing before reuse. Wash hands before eating, smoking or using the washroom.

SECTION IX

STORAGE AND HANDLING INFORMATION

Storage Temperature: Max 60°C/140°F Min 5°C/40°F

Precautionary Handling: Keep from freezing; product may coagulate. Keep material from direct sunlight. Store in a sheltered area.

SECTION X

TOXICITY INFORMATION

Ethylene glycol has been shown to produce dose-related teratogenic effects in rats and mice at high concentrations. Sanding dust inhalation may cause lung damage. Crystalline silica has been classified as probably carcinogenic for humans. Titanium dioxide as formulated in this product, does not pose a dust hazard unless sanding or grinding of the dry coating takes place. TLV and PEL for inorganic filler and silica sand are those for nuisance dusts. See Section II.

**MATERIAL SAFETY DATA SHEET – COLOR SEAL™
EL REY STUCCO**

Page 4 of 4

SECTION XI	REGULATORY INFORMATION	
-------------------	-------------------------------	--

WORKPLACE CLASSIFICATIONS: This product is considered non-hazardous under the OSHA Hazard Communication Standard (29CFR 1910.1200). This product is not a controlled product under the Canadian Workplace Hazardous Materials Information System (WHMIS).

EMERGENCY PLANNING & COMMUNITY RIGHT-TO-KNOW (SARA TITLE 3):

Section 311/312 Categorizations (40CFR 370): This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.

Section 313 Information (40CFR 372): This product does not contain a chemical, which is listed in Section 313 above deminimis concentrations.

CERCLA INFORMATION (40CFR 302.4): Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

RCRA INFORMATION: When this product becomes a waste, it is classified as a non-hazardous waster under criteria of the Resource Conservation and Recovery Act (40 CFR 261).

CHEMICAL CONTROL LAW STATUS: All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

STATE RIGHT-TO-KNOW LAWS: Not applicable.

TRANSPORTATION CLASSIFICATION: US DOT: Hazard Class.....NONREGULATED

SECTION XII	ADDITIONAL INFORMATION	
--------------------	-------------------------------	--

n.e. = Not established; **n.a.** = Not applicable/not available; **n.d.** = Not determined; **NOS** = Not Otherwise Specified; **RQ** = Reportable Quantity; **resp.** = Respirable dust; **TLV** = Threshold Limit Value; **PEL** = Permissible Exposure Limit; **STEL** = Short Term Exposure Limits (15 minutes); **TWA** = Time Weighted Average (8 hour); **ANSI** = American National Standards Institute; **REL** = Recommended Exposure Limits (developed by the NIOSH); **NIOSH** = National Institute for Occupational Safety and Health; **OSHA** = Occupational Safety and Health Administration; **ACGIH** = American Conference of Governmental Industrial Hygienists; **LEL** = Lower Explosive Limit; **UEL** = Upper Explosive Limit; **ppm** = parts per million; **TSCA** = Toxic Substance Control Act; **SARA** = Superfund Amendments and Reauthorization Act; **DOT** = Department of Transportation. **WHMIS** = Workplace Hazardous Materials Information System (Canadian).

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. ParexLahabra, Inc. assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.

Date: March 13, 2002