



MATERIAL SAFETY DATA SHEET

MANUFACTURER: PAREXLAHABRA, INC.
ADDRESS: EI REY STUCCO
4100^{1/2} BROADWAY S.E.
ALBUQUERQUE, NM 87105
TELEPHONE: (505) 873-1181

DATE: March 15, 2002

Page 1 of 4

IN CASE OF SPILL EMERGENCY, DAY OR NIGHT, CALL CHEMTREC 1-800-424-9300

SECTION I PRODUCT IDENTIFICATION

IDENTITY: CONCENTRATE, P-F 400 LIQUID

SECTION II COMPOSITIONAL INFORMATION

<u>Ingredients</u>	<u>CAS Reg. No.</u>	<u>OSHA TWA/TLV</u>	<u>ACGIH TWA/TLV</u>
Modified Acrylic Polymer	Non Hazardous	n.e.	n.e.
Proprietary Ingredients	Non Hazardous	n.e.	n.e.
Water	Non Hazardous	n.a.	n.a.

SECTION III PHYSICAL PROPERTY INFORMATION

Boiling Point: >100°C (212°F)
Freezing Point: 0°C/32°F
Viscosity: Variable
Vapor Density (Air=1): >1
Specific Gravity: 1.04 – 1.07
Solubility in Water: Dilutable
Appearance: Milky white liquid
Odor: Slight ammonia odor
pH: 9 - 10

SECTION IV FIRE AND EXPLOSION HAZARD INFORMATION

Flammable Class: 3B

Flash Point (Method): n.a.

Flammable Limits:

LEL: n.a.

UEL: n.a.

Extinguishing Media: Water, carbon dioxide or dry chemical.

Special Fire Fighting Procedures: Fire Fighters and others exposed to vapors or products of combustion should wear self-contained breathing apparatus.

Unusual Fire & Explosion Hazards: This material may generate formaldehyde when heated.

MATERIAL SAFETY DATA SHEET
EL REY STUCCO – CONCENTRATE, P-F 400 LIQUID

SECTION V

HEALTH HAZARD INFORMATION

PERMISSIBLE EXPOSURE LEVEL

This material may release formaldehyde fumes when heated or cured. The ACGIH TLV and the OSHA PEL for formaldehyde are 1 ppm for an 8-hour TWA and a 2 ppm STEL for a 15 minute period. Workplace with formaldehyde levels of 0.5 ppm (TWA) or greater may be subject to the monitoring and medical surveillance requirements of 29 CFR 1910.1018. There is no OSHA PEL or ACGIH TLV established for the modified acrylic polymer in this mixture.

PRIMARY ROUTE (S) OF ENTRY: Inhalation of vapors (especially if sprayed or heated).

EFFECTS OF OVER-EXPOSURE

Inhalation: Vapors or mist can cause irritation of the mucous membranes of the nose, throat, and respiratory tract. It may also cause headaches and nausea.

Skin Contact: May be irritating to the skin upon repeated or prolonged contact.

Eye Contact: Product may be irritating to the eye.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

EMERGENCY AND FIRST AIR PROCEDURES

Inhalation: Remove victim to fresh air immediately. If coughing, difficult breathing or any other respiratory symptoms develop, seek medical attention at once.

Skin and Eye Contact: Wash affected area with soap and water. Flush eye with large amounts of water for fifteen minutes.

Ingestion: If ingested, seek medical attention immediately.

HAZARDOUS RATING: (For material as packaged)

Health/Toxicity	1
Flammability	0
Reactivity	0
Personal Protection	G

SCALE:

4 = Sever
3 = Serious
2 = Moderate
1 = Slight
0 = Minimal

NOTE: HMIS, NFPA and El Rey ratings involve data and interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

Hazardous Materials Identification System and HMIS are registered trademarks of the National Paint and Coatings Association.

SECTION VI

REACTIVITY INFORMATION

Stability: Under normal conditions the product is stable.

Incompatibility: None known.

Hazardous Decomposition or Byproducts: Temperatures above 177°C/350°F may cause the acrylic polymer to decompose.

MATERIAL SAFETY DATA SHEET
EL REY STUCCO – CONCENTRATE, P-F 400 LIQUID

Page 3 of 4

SECTION VI (continued)	REACTIVITY INFORMATION
-------------------------------	-------------------------------

Hazardous Polymerization: Will not occur; however, under severe thermal degradation – low molecular weight organic compounds will be formed.

SECTION VII	SPILL OR LEAK PROCEDURE INFORMATION
--------------------	--

Keep spectators away as area of leak or spill may be slippery. Dike and contain the spill or leak with inert materials, e.g. sand, earth. Transfer the liquid to containers for recovery or disposal. If needed, the area can be flushed with water. All contaminated materials (product and absorbing medium) should be disposed of in accordance with pertinent Federal, State and local government regulations. Take extra care to insure none of the cleaning water gets into the sanitary or storm sewers and open bodies of water. Remove contaminated clothing promptly and wash affected skin areas with soap and water.

SECTION VIII	PERSONAL PROTECTION INFORMATION
---------------------	--

Ventilation Type: There should be plenty of natural airflow in the work area. In the event of a spill in an enclosed area, utilize a mechanical system to induce airflow.

Respiratory Protection: None required if there is good ventilation; otherwise wear a respirator (OSHA/NIOSH approved or equivalent) suitable for concentration and contaminants involved.

Protective Gloves: Chemical-resistant nitrile, neoprene or rubber gloves required.

Eye Protection: Wear face shield or chemical goggles.

Other Protective Equipment: Wear protective clothing to prevent skin contact. Eye wash station and safety shower should be available.

SECTION IX	STORAGE AND HANDLING INFORMATION
-------------------	---

Storage Temperature: Max 60°C/140°F Min 5°C/40°F

Precautionary Handling: Keep from freezing; product may coagulate or gel. Keep material from direct sunlight. Store in a sheltered area. Keep away from heat or open flame. Avoid prolonged or repeated skin contact.

SECTION X	TOXICITY INFORMATION
------------------	-----------------------------

Toxicological testing has not been conducted with this product. This mixture may generate formaldehyde when heated; and the National Toxicology Program (NTP) and the International Agency list formaldehyde as a potential carcinogen for Research on Cancer (IARC).

SECTION XI	REGULATORY INFORMATION
-------------------	-------------------------------

Formaldehyde is listed by the State of California as a substance known to cause cancer. The California Safe Drinking Water and Toxic Enforcement Act (Proposition 65) requires clean and reasonable warning be given before exposing any person to formaldehyde.

MATERIAL SAFETY DATA SHEET
EL REY STUCCO – CONCENTRATE, P-F 400 LIQUID

Page 4 of 4

SECTION XI (continued)

REGULATORY INFORMATION

SARA & WHMIS Hazard Classifications: This material is not categorized as a hazardous substance as defined by SARA Title III regulations (40 CFR 370).

Canadian WHMIS Classification: Not WHMIS hazardous.

SARA Section 313 Listed Ingredients: The following ingredients in this material are not subject to the reporting requirements of Section 313 of SARA and 40 CFR 372.

TRANSPORTATION CLASSIFICATION: US DOT Hazard Class-NONREGULATED

SECTION XII

ADDITIONAL INFORMATION

n.e. = Not established; **n.a.** = Not applicable/not available; **n.d.** = Not determined; **NOS** = Not Otherwise Specified; **RQ** = Reportable Quantity; **resp.** = Respirable dust; **TLV** = Threshold Limit Value; **PEL** = Permissible Exposure Limit; **STEL** = Short Term Exposure Limits (15 minutes); **TWA** = Time Weighted Average (8 hour); **ANSI** = American National Standards Institute; **REL** = Recommended Exposure Limits (developed by the NIOSH); **NIOSH** = National Institute for Occupational Safety and Health; **OSHA** = Occupational Safety and Health Administration; **ACGIH** = American Conference of Governmental Industrial Hygienists; **LEL** = Lower Explosive Limit; **UEL** = Upper Explosive Limit; **ppm** = parts per million; **TSCA** = Toxic Substance Control Act; **SARA** = Superfund Amendments and Reauthorization Act; **DOT** = Department of Transportation. **WHMIS** = Workplace Hazardous Materials Information System (Canadian).

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. ParexLahabra, Inc. assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.

Revised: March 15, 2002