



MATERIAL SAFETY DATA SHEET

MANUFACTURER : PAREXLAHABRA, INC.
E1 REY STUCCO
ADDRESS : 4100^{1/2} BROADWAY S.E.
ALBUQUERQUE, NM 87105
TELEPHONE : (505) 873-1181

Revised: March 8, 2002

Page 1 of 3

IN CASE OF SPILL EMERGENCY, DAY OR NIGHT, CALL CHEMTREC 1-800-424-9300

SECTION I PRODUCT IDENTIFICATION

IDENTITY: KRAK-MASTER™ MESH

SECTION II COMPOSITIONAL INFORMATION

<u>Ingredients</u>	<u>CAS Reg. No.</u>	<u>APPROX. WT. %</u>	<u>OSHA / PEL</u>	<u>ACGIH / TLV</u>
Fibrous Glass	65997-17-13	100	15mg/m ³ (dust)	10mg/m ³ (dust) 5mg/m ³ (respirable)

Comments: Amounts of dust will be dependent upon method of handling.

SECTION III PHYSICAL PROPERTY INFORMATION

Boiling Point:	n.a.	Specific Gravity (Water = 1):	1.2– 1.3
Melting Point:	>1100 ° C (glass)	Softening Point:	>700°C (glass)
Vapor Pressure:	n.a.	Percent Volatile by Volume:	n.a.
Vapor Density (Air = 1):	n.a.	Evaporation Rate (Butyl Acetate = 1):	n.a.
Solubility in Water:	Insoluble in water	pH:	n.a.
Appearance and Odor:	Woven Fabric, no discernible odor.		

Volatile Organic Content (VOC): 0 %

SECTION IV FIRE AND EXPLOSION HAZARD INFORMATION

Flash Point: >300° F (>149° C) **Autoignition Temperature:** n.a.
Flammable Limits: LEL: n.a. UEL: n.a.
Extinguishing Media: Use dry chemical, water fog, foam, CO₂.
Special Fire Fighting Procedures: If entering a confined area, firefighters should wear NIOSH approved self-contained breathing apparatus.
Unusual Fire and Explosion Hazard: The fiber glass woven fabric will not burn. Data cited are for resin coating.

SECTION V HEALTH HAZARD INFORMATION

EFFECTS OF OVER-EXPOSURE

Inhalation: Permissible Exposure Limit (PEL) value is 15mg/m³ (for nuisance dust).

Skin Contact: Dust/glass fibers may be irritating to the skin. Mechanical irritation possible.

Eye contact: Mechanical irritation.

Medical Condition Aggravated by Exposure: Dermatitis, however sensitivity varies from individual to individual

EMERGENCY AND FIRST AID PROCEDURES

Inhalation: Remove to fresh air. If breathing is difficult give oxygen. Continued difficulty, get medical attention.

Skin Contact: Wash with soap and water or use waterless hand cleaner.

Eye Contact: Flush with large amounts of water while holding eyelids open. Get medical attention, if irritation persists.

Note: Not a carcinogen.

There is no chemical hazard from this material. Excessive fiberglass dust in the air may be irritating to the respiratory tract and eyes, but this is not likely to happen with this material. Shower and clean work clothes daily is recommended.

SECTION VI REACTIVITY INFORMATION

Stability: Stable

Incompatibility: Avoid contact with strong oxidizers.

Hazardous Polymerization: Will not occur.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, aldehydes and other unidentified compounds may form upon combustion of the organic resin finish.

SECTION VII SPILL OR LEAK PROCEDURE INFORMATION

Steps to be taken in case material is released or spilled: No special precautions required

Waste Disposal Method: An inert solid waste. Usually can be disposed of in a sanitary landfill. Check local authorities, if any questions.

SECTION VIII PERSONAL PROTECTION INFORMATION

Ventilation: Normal ventilation is usually adequate.

Respiratory Protection: Not normally required. If deemed necessary, use NIOSH approved dust respirator.

Protective Gloves: If needed, use impervious gloves.

Eye Protection: Safety Glasses or Goggles.

SECTION IX STORAGE AND HANDLING INFORMATION

Precautionary Handling: Store and use in a manner that will prevent airborne particulate in the workplace.

**MATERIAL SAFETY DATA SHEET – KRAK-MASTER™ MESH
EL REY STUCCO**

SECTION X	TOXICITY INFORMATION
------------------	-----------------------------

Toxicological testing has not been conducted with this product.

SECTION X	REGULATORY INFORMATION
------------------	-------------------------------

WORKPLACE CLASSIFICATIONS: This product is considered non-hazardous under the OSHA Hazard Communication Standard (29CFR 1910.1200). This product is not a controlled product under the Canadian Workplace Hazardous Materials Information System (WHMIS).

STATE RIGHT-TO-KNOW LAWS: Not applicable.

TRANSPORTATION CLASSIFICATION: US DOT: Hazard Class.....NONREGULATED

HAZARDOUS RATING: (for material as packaged)		SCALE:
Health/Toxicity	0	4 = Severe
Flammability	1	3 = Serious
Reactivity	0	2 = Moderate
Personal Protection	B	1 = Slight
		0 = Minimal

NOTE: HMIS, NFPA, and El Rey ratings involve data and interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

SECTION XI	ADDITIONAL INFORMATION
-------------------	-------------------------------

n.e. = Not established; n.a. = Not applicable/not available; n.d. = Not determined; NOS = Not Otherwise Specified; RQ = Reportable Quantity; resp. = Respirable dust; TLV = Threshold Limit Value; PEL = Permissible Exposure Limit; STEL = Short Term Exposure Limits (15 minutes); TWA = Time Weighted Average (8 hour); ANSI = American National Standards Institute; REL = Recommended Exposure Limits (developed by the NIOSH); NIOSH = National Institute for Occupational Safety and Health; OSHA = Occupational Safety and Health Administration; ACGIH = American Conference of Governmental Industrial Hygienists; LEL = Lower Explosive Limit; UEL = Upper Explosive Limit; ppm = parts per million; TSCA = Toxic Substance Control Act; SARA = Superfund Amendments and Reauthorization Act; DOT = Department of Transportation. WHMIS = Workplace Hazardous Materials Information System (Canadian).

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. ParexLahabra, Inc. assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.

Date: March 8, 2002