



MATERIAL SAFETY DATA SHEET

MANUFACTURER: PAREXLAHABRA, INC.
EI REY STUCCO
ADDRESS: 4100^{1/2} BROADWAY S.E.
ALBUQUERQUE, NM 87105
TELEPHONE: (505) 873-1181

Revised: August 24, 1994

Page 1 of 3

IN CASE OF SPILL EMERGENCY, DAY OR NIGHT, CALL CHEMTREC 1-800-424-9300

SECTION I PRODUCT IDENTIFICATION

IDENTITY: PERMA-FLEX® 400 (Masonry Surface Conditioner/Primer)

SECTION II COMPOSITIONAL INFORMATION

<u>Ingredient</u>	<u>CAS Req No.</u>	<u>APPROX. WT. %</u>	<u>TWA/TLV</u>
Acrylic Polymer	Non Hazardous	40 max.	n.e.
Texanol	25265-77-4	0.5 max.	n.e.
Ammonium Hydroxide	1336-21-6	1.0 max.	25 ppm
Water	Non Hazardous	80 max.	n.e.

SECTION III PHYSICAL PROPERTY INFORMATION

Boiling Point:	Variable	Specific Gravity:	1.01 ± 0.01
Freezing Point:	0°C/32°F	Solubility in Water:	Dilutable
Viscosity:	Variable	Appearance:	Milky white liquid
Vapor Density:	<1	Odor:	Slight ammoniacal odor
pH:	8-10		

SECTION IV FIRE AND EXPLOSION HAZARD INFORMATION

Non-Flammable, Non Explosive
Material can splatter above 100°C/212°F
Dried polymer film can burn.

SECTION V HEALTH HAZARD INFORMATION

EFFECTS OF OVER-EXPOSURE

Inhalation: Vapors or mist can cause irritation of the mucous membranes of the nose, throat and respiratory tract. It may also cause headaches and nausea.

Skin Contact: May be irritating to the skin upon repeated or prolonged contact.

Eye contact: Product may be irritating to the eye.

MATERIAL SAFETY DATA SHEET - PERMA-FLEX® 400
(MASONRY SURFACE CONDITIONER/PRIMER)
EL REY STUCCO

Page 2 of 3

SECTION V (continued)	HEALTH HAZARD INFORMATION
------------------------------	----------------------------------

EMERGENCY AND FIRST AID PROCEDURES

Inhalation: Move subject to fresh air.

Skin and Eye contact: Wash affected area with soap and water.

Flush eye with large amount of water for fifteen minutes.

Note: If irritation persists, contact a physician. If accidentally ingested contact a physician.

SECTION VI	REACTIVITY INFORMATION
-------------------	-------------------------------

Under normal conditions the product is stable. However, temperatures above 177°C/350°F may cause the acrylic polymer to decompose. There are no hazardous decomposition by-products, nor will hazardous polymerization occur.

SECTION VII	SPILL OR LEAK PROCEDURE INFORMATION
--------------------	--

Keep spectators away as area of leak or spill may be slippery. Dike and contain the spill or leak with inert materials, eq. sand, earth. Transfer the liquid to containers for recovery or disposal. If needed, the area can be flushed with water. All contaminated materials (product and absorbing medium) should be disposed of in accordance with pertinent Federal, State and local government regulations. Take extra care to insure none of the cleaning water gets into the sanitary or storm sewers and open bodies of water. Remove contaminated clothing promptly and wash affected skin areas with soap and water.

SECTION VIII	PERSONAL PROTECTION INFORMATION
---------------------	--

Ventilation Type: There should be plenty of natural air flow in the work area. In the event of a spill in an enclosed area, utilize a mechanical system to induce air flow.

Respiratory Protection: None required if there is good ventilation; otherwise wear a respirator (MSHA/NIOSH approved or equivalent) suitable for concentration and type of contaminants encountered.

Protective Gloves: Normally not required.

Eye Protection: Normally not required, however clear safety glasses or goggles may be used (ANSI Z87.1 approved or equivalent).

SECTION IX	STORAGE AND HANDLING INFORMATION
-------------------	---

Storage Temperature: Max 60°C/140°F

Min 5°C/40°F

Precautionary Handling: Keep from freezing; product may coagulate or gel. Keep material from direct sunlight. Store in a sheltered area.

MATERIAL SAFETY DATA SHEET - PERMA-FLEX 400
(MASONRY SURFACE CONDITIONER/PRIMER)
EL REY STUCCO

Page 3 of 3

SECTION X	TOXICITY INFORMATION
------------------	-----------------------------

Toxicological testing has not been conducted with this product.

SECTION XI	ADDITIONAL INFORMATION
-------------------	-------------------------------

n.e. = Not established; n.a. = Not applicable/not available; n.d. = Not determined; NOS = Not Otherwise Specified; RQ = Reportable Quantity; resp. = Respirable dust; TLV = Threshold Limit Value; PEL = Permissible Exposure Limit; STEL = Short Term Exposure Limits (15 minutes); TWA = Time Weighted Average (8 hour); ANSI = American National Standards Institute; REL = Recommended Exposure Limits (developed by the NIOSH); NIOSH = National Institute for Occupational Safety and Health; OSHA = Occupational Safety and Health Administration; ACGIH = American Conference of Governmental Industrial Hygienists; LEL = Lower Explosive Limit; UEL = Upper Explosive Limit; ppm = parts per million; TSCA = Toxic Substance Control Act; SARA = Superfund Amendments and reauthorization Act; DOT = Department of Transportation.
WHMIS = Workplace Hazardous Materials Information System (Canadian).

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. ParexLahabra, Inc. assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.

Revised: August 24, 1994