



Liquid Colorant

DESCRIPTION:

- A. Pre-packaged liquid color composed of pigments and dispersing agents to be mixed into EL REY[®] Perma-Flex[®] Acrylic Stucco Finishes.
- B. Features and Benefits to using Liquid Colorant are:
 - Portable and convenient packaging, making stocking and inventorying product much easier.
 - Enables jobsite tinting
 - Minimum mixing required, decreasing application time and associated costs.

USES:

- A. For use with El Rey Perma-Flex Acrylic Stucco Finishes. Not for use with portland cement based products.

COMPOSITION AND PHYSICAL PROPERTIES:

- A. Single component liquid.
- B. VOC: <=605 g/l.

COVERAGE:

- A. See Perma-Flex Acrylic Stucco Finish datasheet.

PACKAGING:

- A. 4 or 8 oz. bottle depending on color.
- B. Storage: Protect from heat and freezing at all times.
- C. Keep container closed when not in use.
- D. Shelf life: One year if protected from sun and freezing.

JOB PREPARATION

A. Preparation:

1. Shake well before using.

B. Mixing:

1. Add entire contents to proper 60-pound (27.2 kg) acrylic stucco finish base (white, tint or deep); this will require rinsing container with water. Do not use more than a total of 8-fluid ounces of rinse water.
2. Stir with LOW SPEED electric drill 100-150 RPM maximum. DO NOT ENTRAIN AIR. Stir thoroughly until uniform.
3. After mixing, check to insure proper color is obtained before applying.

ParexLahabra, Inc./El Rey Stucco is not responsible for color correctness of applied products.

C. Application:

1. Please see the Perma-Flex® Acrylic Stucco Finish datasheet for application instructions.

Limitations:

1. Use in a well ventilated area. Direct contact or vapors can cause headache, nausea and irritation of the nose, throat, lungs, eyes and skin. Refer to Material Safety Data Sheet (MSDS) for further information.
2. Use rubber gloves, respiratory and eye protection when handling this product.
3. Keep product out of the reach of children.

Job Name _____

Contractor _____

Date _____

Submittal Approvals: _____

Stamps or Signatures _____

El Rey
Stucco

www.elrey.com

El Rey Sales Office

3830 Singer Blvd. NE
Suite 2020
Albuquerque, NM 87109
Phone: (505) 873-1180
Fax: (505) 345-9009

Albuquerque Plant

4100 1/2 Broadway SE
Albuquerque, NM 87105
Phone: (505) 873-1181
Fax: (505) 877-6670

Colorado Springs Plant

3225 S. Drennan Industrial Loop
Colorado Springs, CO 80910
Phone: (719) 392-9003
Fax: (719) 392-6346

Corporate Office

ParexLahabra, Inc.

4125 E. La Palma, Suite 250
Anaheim, CA 92807
Phone: (714) 778-2266
Fax: (714) 774-2079